

6 GALLON MIXER

AUTO TIMER EQUIPPED

HoverTrowel Inc.

5048 Spruce Lane
Mohnton, PA 19540
Phone (610) 856-1961
Fax (610) 856-1920
www.hovertrowel.com
sales@hovertrowel.com



HEAVY- DUTY

The gear box is attached directly to Electric Motor. First stage gearing is helical cut to reduce high-speed noise. The second stage spur gearing includes a steel pinion and cast iron output gear. All gears are supported by ball bearings.

AUTO TIMER

Repeat cycle timer on the handle is useful when mixing decorative aggregate systems. The adjustable repeat cycle timer ranges from 15 seconds to 10 minutes

VERSATILE

Designed tough enough to mix epoxies; even with added aggregate. Other uses include mixing of grouts, mortars, plaster, cements, paint, adhesives, etc.

LIGHTWEIGHT

Generous use of aluminum makes for both a strong and lightweight unit. Net weight is only 71 pounds and the 8-inch tires allow for easy mobility.

WKRM SPECIFICATIONS

MIXING CAPACITY	1/2 Cubic Foot / 3 3/4 Gallons
MOTOR H.P.	1/2 Direct Drive
DRUM RPM	60
VOLTAGE	115
WEIGHT	71 lbs
TIMER RANGE	15 Seconds to 10 Minutes
MEASUREMENTS	42" H x 22" W x 27" L