



SCB-1200 W/SC-12 Scarifier Head Attachment



SCB-1200-E
Electric 230V/480V
W/SC-12 Scarifier Head Attachment



SCB-1200-D
Turbo Diesel
W/SC-12 Scarifier Head Attachment

Information

After years of research, development and testing, B W Manufacturing, Inc. has produced the only mid-sized ride on scarify/shotblast/diamond grind-polish machine in the market today. With a state of the art scarifying head that is self leveling to automatically adjust itself to different contours of the floor or pavement. You will achieve an accurate removal of thin mill coatings to 1/4" overlays. The SCB-1200 W/SC-12 Scarifier Head Attachment is ideal for use on rubber membranes, mastics, epoxy coatings, and line stripes. The SCB-1200 W/SC-12 Scarifier Head Attachment gives you mobility and versatility by being able to switch from scarifying to blasting in just minutes.

The SCB-1200 W/SC-12 Scarifier Head Attachment will put you ahead of the competition with its production rates and it's vacuum/collector system that eliminates dust and removes all material from the surface it is scarifying.

The SCB-1200 W/SC-12 Scarifier Head Attachment has an easy to turn manual steering and ergonomically designed one handed controls, along with a removable dust containment box with wheels for ease of dumping.

Versatility is the key to the SCB-1200 W/SC-12 Scarifier Head Attachment. With quick change cages you can go from steel to carbide cutters and to different cutting width cages in just minutes.

Using the latest technology in EPA approved liquid cooled diesel engines and catalytic converter, you are far below any minimal emissions standards. With the use of state of the art components, compressors, electronic pulsation, hydraulics, and drives, the SCB-1200 is the most reliable and productive surface preparation machine on the market today!



Chassis/Specifications

<u>Interchangeable Head:</u>	Shotblast Scarifier Diamond Grinder Non-marking
<u>Tires:</u>	
<u>Length:</u>	81"
<u>Width:</u>	35"
<u>Height:</u>	54"
<u>Weight:</u>	1200 lbs.
<u>Engine (Turbo Diesel):</u>	36 hp
<u>Motor (230V/480V):</u>	25 hp
<u>3 Phase 230V 64 amps</u>	"
<u>3 Phase 480V 32 amps</u>	"
<u>Drive:</u>	Hydrostat
<u>Compressor:</u>	4.5 cfm.
<u>Vacuum:</u>	1480 cfm.
<u>Steering:</u>	Manual
<u>Collector Capacity:</u>	3.8 cubic ft.
<u>Aisle Width Min:</u>	54" (Blastable Width)

Scarifier/Specifications

<u>Production Capacity:</u>	500 to 1000 sfh
<u>Cleaning Path:</u>	4" to 12"
<u>Width with attachment:</u>	40"
<u>Weight:</u>	420 lbs.

Scarifier Applications

- Industrial floors
- Bridge decks
- Parking decks
- Line stripes
- Block floors
- Rubber membranes Highways

Accessories



10129-B

Blend Filter (standard)
99.7% Efficiency @ .05 Microns



10129-D

Moisture Resistant (optional)
99% Efficiency @ 1-2 Microns

10129-H

HEPA (optional) (Special Order)
99.995% Efficiency @ .03 Microns



Cage W/ Steel Cutters

S-012-DAS

Cage W/Steel Cutters



Cage W/ Carbide Cutters

S-012-DAC

Cage W/Carbide Cutters



A-16C12

12 Point Carbide Cutter
(Requires 168 per cage)



SC-1630

Steel Cutters
(Requires 240 per cage)



All Major Credit Cards Accepted and Secured by:



Distributed by:

HoverTrowel, Inc.

5048 Spruce Lane, Mohnton, PA 19540
Phone: 610-856-1961 Fax: 610-856-1920

Email: sales@hovertrowel.com

Web Site: www.hovertrowel.com

